



## AS 1000 Series Technical Specifications

### 1-3 kVA 1 Phase Input - 1 Phase Output (HF) Online UPS

MODEL	AS 1001	AS 1001L	AS 1002	AS 1002L	AS 1003	AS 1003L
Rated Power (kVA)	1 kVA		2 kVA		3 kVA	
Active Power (kW)	0,9 kW		1,8 kW		2,7 kW	
<b>INPUT</b>						
Rated Voltage	200/208/220/230/240 Vac (1P+N+PE)					
Voltage Range	125~290±%5@0-60% Rated Load 155~290±%5@70-80% Rated Load		135~290±%5@60-70% Rated Load 175~290±%5@80-100% Rated Load			
Operating Frequency Range	40/70 Hz					
Power Factor	0,99					
<b>OUTPUT</b>						
Rated Voltage	200/208/220/230/240 Vac (1P+N+PE)					
Voltage Regulation	±1%					
Frequency	Line	47-53 Hz or 57-63 Hz (Synchronized Range)				
	Battery	50/60±0,1 Hz				
Waveform	Pure Sine Wave					
Voltage Distortion (THDv)	<3% (linear load); <6% (Non-linear load)					
Output Power Factor	0,9					
Crest Factor	3:1					
Efficiency	Line Mode	88%		92%		
	Battery Mode	85%	86%	87%	88%	90%
<b>SYSTEM FEATURES</b>						
UPS Type / Technology	Standalone Tower Type / True Online Double Conversion					
Transfer Time	AC - Battery	Zero				
	INV - Bypass	4 ms (Typical)				
Overload Capability	Ambient Temp < 35 °C	105%-110%: UPS shuts down after 10 minutes at battery mode or transfer to bypass when the utility is normal 110%-130%: UPS shuts down after 1 minutes at battery mode or transfer to bypass when the utility is normal >130%:UPS shuts down after 3 seconds at battery mode or transfer to bypass when the utility is normal				
	40°C < Ambient Temp < 35°C	105%-110%: UPS shuts down after 1 minutes at battery mode or transfer to bypass when the utility is >110%:UPS shuts down after 3 seconds at battery mode or transfer to bypass when the utility is normal				
Short Circuit	Hold Whole System					
Overheat	Line Mode: Switch to Bypass; Backup Mode: Shut down UPS immediately					
Low Battery Voltage	Alarm and Switch Off					
EPO (optional)	Shut down UPS Immediately					
Communication Interface	USB (or Rs232), SNMPcard (optional) Relay card (optional)					
Audible & Visual Alarms	Line Failure, Battery Low Overload, System Fault					
<b>BATTERY</b>						
Rated Voltage / Capacity	2x12V/9 Ah		4x12V/9 Ah		6x12V/9 Ah	
Typical Charge Time	4 Hours to %90 Capacity					
<b>ENVIRONMENT</b>						
Operating Temperature	0°C to 40 °C					
Storage Temperature	-25°C to 55°C					
Relative Humidity	< 20-95% @ 0°- 40 °C (non-condensing)					
Altitude	< 1500 m					
Audible Noise	< 50 dBA					
<b>STANDARDS</b>						
LVD (Safety)	IEC/EN 62040-1 / IEC/EN 60950-1					
EMC	IEC/EN 62040-2/IEC61000-4-2/IEC61000-4-3/IEC61000-4-4/IEC61000-4-5/IEC61000-4-6/IEC61000-4-8					
<b>PHYSICAL</b>						
Dimensions (WxDxH) [mm]	144x293x209		144x399x209		191x460x337	144x399x209
Weight [kg]	9,8	4,1	17	6,8	27,6	7,4

### FEATURES

- True double-conversion
- Wide input voltage range (110-300 Vac)
- Input power factor correction 0.99
- Output Power Factor 0.9
- Maximum 12A charger for long-run models
- Charger current can be setting by LCD
- 50Hz/60Hz frequency converter mode
- Emergency power off function (EPO)
- Eco mode operation for energy saving (ECO)
- Generator compatible
- SNMP / USB / RS232 multiple communications
- Smart battery charger design for optimized battery performance
- Selectable output voltage: 200, 208, 220, 230, 240Vac

### ONLINE UPS

AS 1000 Series, produced with PWM and IGBT technology provide sinusoidal waveform output and contains advanced communication options. These series are 1 phase input, 1 phase output online UPS. AS 1000 Series manufactured in different power ranges, are used to supply vital important equipment's such as medical analysis equipment's, operating rooms in hospitals, ultrasound equipment's, security systems, all kinds of automation systems, computer networks and communication systems. Thanks to higher protection providing technology. AS 1000 series protect them from problems of utility failures and irregular voltage.